| | © Co | terial Compo pyright 2005. IPC, Bannoc nternational and Pan-Ameri | kburn, Illinois | . All rights reserve | tion with lower | level p | arts, the | declaratio | on encon | npasses | all lower | level mate | erials for | which th | e item is an assembly ne manufacturer has eclaration. |
|--|------------|---|-----------------|------------------------------|------------------------|---------------|--------------------------|-------------------------------|---|---|----------------------------------|------------|------------|-----------|---|
| 1/32-2 1.1 | | Web Site for Informat | | -1752 Standa | 71 | | | | laration Class * ss 6 - RoHS Yes/No, Homogeneous Materials and Mfg Informa | | | | | | |
| Supplier Information | | | | | | | | | | | | | | | |
| Company Name * | | Company Unique ID | | Unique ID Au | ıthority | Respo | nse Date | * | | Respons | se Docum | nent ID | | | |
| Anaren Microwave | | | | | | 2019-0 | 08-08 | | | | | | | | |
| Contact Name * Title - Contact | | | | Phone - Contact * | | | - Contac | t * | | | l' . | 2 | A (1 | | |
| Sarvesh Nair Project Engineer | | | | 315-233-5510 | | | sarvesh.nair@ttm.com | | | | plicate | Contact | -> Autho | orized Re | presentative |
| Authorized Representative * Title - Representative | | | Э | Phone - Representative * | | | Email - Representative * | | | Supplier Comments or URL for Additional Information | | | | | |
| Sarvesh Nair Project Engineer | | | | 315-233-5510 | | | sh.nair@ | tm.com | 1 | | | | | | |
| Requester Item Number | | Mfr Item Number | | Mfr Item Name | Effective Date Version | | | Manufa | facturing Site Weig | | Weight * | UC | DM | Unit Type | |
| | C100N50Z4B | | | Surface Mour | nt Termination, 10 | 02019-08-08 A | | | Suzhou, China | | | 0.093 | g | | Each |
| Alternate Recommenda | ation | | | | | | | Alternate | Item Co | mments | | | | | • |
| Manufacturing Proces | s In | formation | | | | | | | | | | | | | |
| Terminal Plating / Grid Array Material Terminal B | | | ase Alloy | ating Peak Process Body Temp | | | Tempera | perature Max Time at Peak Tem | | | perature Number of Reflow Cycles | | | | |
| Matte Tin (Sn) - with Nickel (Ni) barrier Other | | | | | | | 260 C | | 30 se | | econds | 3 | | | |
| Comments | • | | l | | 1 | | | | | | | | | | |
| Compliant to RoHS 2 Dir | ectiv | e 2011/65/EU of the | Europear | Parliament a | and of the Counc | il of 8 | June 201 | 1 & Com | nmissio | n Deleg | ated Dire | ective 20 | 15/863/E | U of 31 | March 2015. |

Save the fields in Import fields from a Clear all of the Lock the fields on this **Export Data** Import Data Reset Form Lock Supplier Fields this form to a file file into this form fields on this form form to prevent changes **RoHS Material Composition Declaration Declaration Type *** Custom Rohs Directive Rohs Definition: Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury, Hexavalent Chromium, Polybrominated Biphenvls (PBB). Polybrominated Diphenyl Ethers (PBDE) and quantity limit of 0.01% by mass (100 PPM) of homogeneous material for Cadmium 2002/95/EC RoHS 2 (Directive 2011/65/EU & 2015/863/EU) Definition Addendum: Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Bis(2-ethylhexyl) phthalate (DEHP), Butyl benzyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP). Supplier certifies that it gathered the information it provides in this form concerning RoHS restrictive substances using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. Supplier Acceptance * Accepted 1 - Item(s) does not contain RoHS restricted substances per the definition above **RoHS Declaration *** Exemptions: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions. **Declaration Signature**

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

Homogeneous Material Composition Declaration for Electronic Products

Subltem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

| Item/SubItem | | Homogeneous | Weight | Unit of | | | Laval | Substance Category | | | Substance | CAS | Exempt | Woight | | Tolerance | | PPM |
|------------------|-------|------------------|----------|------------|----|----|----------|---------------------|----|----|---------------------------|-------------|--------|----------|---------|-----------|---|--------|
| Name | | Material | weight | Measure | | | Level | Substance Category | | | Substance | CAS | Exempt | weight | Measure | - | + | PPIWI |
| +I -I C100N50Z4B | +M -M | Substrate | 0.08484 | lg | +C | -C | Supplier | Substrate | +S | -S | Aluminum Nitride (ALN | 24304-00-5 | | 0.080599 | g | | | 950,00 |
| | | | | | +C | -C | Supplier | Substrate | +S | -S | Yttrium (III) oxide (Y2O3 | 1314-36-9 | | 0.004242 | g | | | 50,000 |
| | +M -M | Conductor | 0.00356 | lg | +C | -C | Supplier | Conductor | +S | -S | Silver (Ag) | 7440-22-4 | | 0.003240 | 9 | | | 910,00 |
| | | | | | +C | -C | Supplier | Conductor | +S | -S | Cobalt (Co) | 7440-48-4 | | 0.000053 | g | | | 15,000 |
| | | | | | +C | -C | Supplier | Conductor | +S | -S | Titanium (Ti) | 7440-32-6 | | 0.000267 | g | | | 75,000 |
| | +M -M | Thick Film Resis | 0.00065 | J g | +C | -C | Supplier | Thick Film Resistor | +S | -S | Boron Oxide (BO) | 1303-86-2 | | 0.000083 | g | | | 129,04 |
| | | | | | +C | -C | Supplier | Thick Film Resistor | +S | -S | Magnesium Oxide (MgC | 1309-48-4 | | 0.000098 | g | | | 151,01 |
| | | | | | +C | -C | Supplier | Thick Film Resistor | +S | -S | Aluminum Oxide (Al2O3 | 1344-28-1 | | 0.000083 | g | | | 129,04 |
| | | | | | +C | -C | Supplier | Thick Film Resistor | +S | -s | Silicon Dioxide (SiO2) | 14808-60-7 | | 0.000031 | g | | | 49,191 |
| | | | | | +C | -C | Supplier | Thick Film Resistor | +S | -S | Ruthenium(IV) dioxide (| 12036-10-1 | | 0.000265 | g | | | 408,59 |
| | | | | | +C | -C | Supplier | Thick Film Resistor | +S | -S | Zinc oxide (ZnO) | 1314-13-2 | | 0.000086 | g | | | 133,11 |
| | +M -M | Protective Glaze | 0.00085 | g | +C | -C | Supplier | Protective Glaze | +S | -s | Boron Oxide (BO) | 1303-86-2 | | 0.000184 | 9 | | | 214,30 |
| | | | | | +C | -C | Supplier | Protective Glaze | +S | -s | Aluminum Oxide (Al2O3 | 1344-28-1 | | 0.000055 | g | | | 64,300 |
| | | | | | +C | -C | Supplier | Protective Glaze | +S | -s | Silicon Dioxide (SiO2) | 14808-60-7 | | 0.000055 | g | | | 64,300 |
| | | | | | +C | -C | Supplier | Protective Glaze | +S | -s | Chromium(III) oxide (Cr | 1308-38-9 | | 0.000012 | g | | | 14,200 |
| | | | | | +C | -C | Supplier | Protective Glaze | +S | -s | Zinc oxide (ZnO) | 1314-13-2 | | 0.000552 | g | | | 642,90 |
| | +M -M | Protective Polyn | n0.00136 | i g | +C | -C | Supplier | Protective Polymer | +S | -s | *Proprietary Metal Com | Proprietary | | 0.000136 | 9 | | | 100,00 |
| | | | | | +C | -C | Supplier | Protective Polymer | +S | -s | *Proprietary Blue Pigme | Proprietary | | 0.000273 | g | | | 200,00 |
| | | | | | +C | -C | Supplier | Protective Polymer | +S | -S | Cobalt (Co) | 7440-48-4 | | 0.000409 | g | | | 300,00 |
| | | _ | | | +C | -C | Supplier | Protective Polymer | +S | -S | Molybdenum (Mo) | 7439-98-7 | | 0.000546 | g | | | 400,00 |
| | +M -M | Part Marking Ink | 0.00000 | g | +C | -C | Supplier | Part Marking Ink | +S | -S | Titanium dioxide (TiO2) | 13463-67-7 | | 0.000007 | 9 | | | 857,10 |
| | | _ | | | +C | -C | Supplier | Part Marking Ink | +S | -S | Silica amorphous (SiO2 | 7631-86-9 | | 0.000001 | g | | | 142,90 |
| | +M -M | Nickel Plating | 0.00148 | g | +C | -C | A | Lead/Lead Compound | +S | -s | Lead | 7439-92-1 | | 0.000000 | g | | | 499.75 |

| | | +C -C B | Nickel (external applic | + S | -S | Nickel | 7440-02-0 | 0.001483 | g | | 999,50 |
|-------------------|-----------|----------------|-------------------------|------------|----|----------|-----------|----------|---|--|---------|
| +M -M Tin Plating | 0.000411g | +C -C Supplier | Tin Plating | +S | -S | Tin (Sn) | 7440-31-5 | 0.000411 | g | | 1,000,0 |